

HOMESTEAD LUBRICATED PLUG VALVES

Fig. 611 & 612

Standard Opening

Semi-Steel

Straightway - Wrench
Operated

Rectangular Port

U.L. Listed

1/2" thru 4"

200 lb. WOG

150 lb SWP

Test: Air under water 200
p.s.i.g.

U.L. Listed

1' thru 6"



Fig. 612 - Semi-Steel, Flanged



Fig. 611 - Semi-Steel, Screwed

DIMENSIONS		SIZE - INCHES									
		1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"
End to End	A	4 1/4	5	5	6	6 3/4	7 5/8	9	-	-	-
Face to Face	A	5 1/2	6	6 1/2	7	7 1/2	8	9	10 1/2	10 1/2	11 1/2
Flange Diameter	G	4 1/4	4 5/8	5	6	7	7 1/2	9	10	11	13 1/2
Flange Thickness	E	7/16	1/2	9/16	5/8	11/16	3/4	15/16	1	1	1 1/8
Number of drilled holes in flange	Y	4	4	4	4	4	4	8	8	8	8
Number of tapped holes in flange	X	-	-	-	-	-	-	-	-	-	-
Center to Top of Stem (Fig. 611)	D	2 29/32	3 5/16	3 5/16	4	5 1/8	5 13/32	6 17/32	-	-	-
Center to Top of Stem (Fig. 612)	D	2 29/32	2 29/32	3 1/2	4	5 1/8	5 13/32	6 17/32	7 3/4	7 3/4	9 3/16
Length of Lubricant Screw	L	1 9/16	1 9/16	1 9/16	1 9/16	2 1/2	2 1/2	2 1/2	3 5/8	3 5/8	3 5/8
Lubricant Stick Diameter	-	3/8	3/8	3/8	3/8	1/2	1/2	1/2	1/2	1/2	1/2