

Fig. 401M (Flanged) Cast Iron Milliken Plug Valves - Regular Pattern, Full Bore

FEATURES & BENEFITS

- Sealing compound effects a completely leak tight seal
- When open - presents a straight through passage in line with pipeline
- Stops flow after 90° turn
- Unless requested plug valves will be supplied with the standard compound No.90

DIMENSIONAL DRAWINGS




Fig. 401M - Sizes 2" to 4"




Fig. 401MG - Sizes 5" to 6"

DIMENSIONS & WEIGHTS

Dimensions 401M

Nom Size	mm	15	20	25	32	40	50	65	80	100
	in	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
A (401M)	mm	-	-	-	-	-	216	241	283	305
	in	-	-	-	-	-	8 1/2	9 1/2	11 1/8	12
B	mm	102	105	108	124	127	187	206	254	270
D Flanged ANSI 250	in	-	-	4 7/8	5 1/4	6 1/8	6 1/2	7 1/2	8 1/4	10
Wrench		G	G	G	J	J	L	L	O	P
Weight (401M)	kg	3.0	3.7	5.0	5.6	7.0	15	17	28	51

Dimensions 401MG (with gear unit)

Nom Size	mm	125	150
	in	5	6
A	mm	381	403
	in	15	15 7/8
B	mm	381	473
D Flanged ANSI 250	in	11	12 1/2
Weight	kg	92	120