

(index.php)

## Lift Check Valves




Ratings :-150 #, 300 #, 600 #, 800 #, 900 #, 1500 # & PN 10 to PN 100

### CS NON RETURN ( LIFT CHECK ) VALVE - PN - 40

No.	Description	Quantity	Material
1	BODY	1	ASTM A 216Gr. WCB
2	BODY RING	1	S.S.AISI 410 / STELLITED ST-6
3	STOPPER	1	S.S.AISI 410 / STELLITED ST-6
4	STUD & NUT	As Required	ASTM A 193 Gr. B7 & ASTM A 194 Gr.2H
5	PIN	1	S.S.AISI 410
6	SPRING	1	SPRING STEEL
7	COVER PLATE	1	ASTM A 216Gr. WCB

### PN - 40

SIZE NB	A	D	C	B	H
15	130	95	14	115	200
20	150	105	16	115	200
25	160	115	16	135	200
32	180	140	18	135	230
40	200	150	18	150	250
50	230	165	20	150	255
65	290	185	20	220	310
80	310	200	22	220	342
100	350	220	24	295	440
125	400	250	26	295	460
150	480	285	26	295	498
200	600	340	30	390	685
250	730	405	32	390	710
300	850	460	32	390	820



[Download! \(pdf/FSLCV800.pdf\)](#)

### Design Features / Options

- Manufacturing Standards - DIN 3356 F1
- Face to Face As Per DIN 3202
- Testing As Per BS 6755
- Also available in Alloy Steel & Stainless Steel.
- Also available with Stellite Seat.
- Available with IBR APPROVED CERTIFICATE IN FORM TC-III

### TEST PRESSURE Kg / Cm2 HYDROSTATIC

CLASS	Body	Seat & Back Seat	AIR Seat
PN - 40	63	40	6

