

Technical Specification :

- 1.Design and manufacture : API 602
- 2.Socket welding dimension : ANSI B1 20.1
- 4.Inspection and test : API 598

Performance Specification

Nominal pressure		800LB	
Test Pressure	Shell test	21.0	MPa
	Tightness test	15.4	
	Gas-Tightness test	0.6	
Max. working temperature		425°C	
Applicable medium : Water, Oil, Gas, acid			

GLOBE VALVE CLASS800

SIZE	L	H	W	d1
1/2"	73	152	100	11
3/4"	80	158	100	13
1"	100	195	125	17
1 1/4"	114	226	160	22
1 1/2"	145	238	160	28
2"	160	286	180	33

MAIN PARTS AND MATERIALS

9	Gland eyeboltt	B8M	18	Seat	316
8	Gland	316	17	Packing	Graphite
7	Pin	316	16	Packing	Graphite
6	Bolt	B8M	15	Handwhell	A197
5	Bonnet	316	14	Name Plate	LY12
4	Gasket	316+Graphite	13	Nut	A194 2H
3	Stem	316	12	Tesm Nut	A276 410
2	Disc	316	11	Nut	316
1	Body	316	10	Gland Flange	316
NO	Part name	Material	NO	Part name	Material

图样标记	重量	比例
	mm	1:1

标记	处数	更改文件号	签字	日期
设计			审核	
校对			标准化	
工艺			批准	
			日期	

名称 GLOBE Valve

PTV[®]
Solutions

