



- The technical requirements
1. Design standard : ASME B16.34
 2. Inspection and test : API598 ;
 3. Thread end :NPT
 4. Working Pressure:15MPa
 5. Temperature Range:-20~210°C

PTV[®]
Solutions

Configuration Dimension :

Size	DN	D	L	H	T	C	IS05211
1/2"	15	15	62	60	100	9	F03
3/4"	20	20	71	64	110	11	F04/05
1"	25	25	80	77	137	11	F04/05
1 1/2"	40	38	105	90	163	14	F05/07
2"	50	50	120	102	172	14	F05/07
2 1/2"	65	65	145	128	210	17	F07/10
3"	80	80	168	135	212	17	F07/10

MAIN PARTS AND MATERIALS

NO	Part name	Material	QTY	NO	Part name	Material	QTY
7	Gland	SS201	1	14			
6	Packing	RPTFE	1	13	Lock	SS201	1
5	Thrust washer	RPTFE	1	12	Handle Cover	PVC	1
4	Joint Gasket	RPTFE	1	11	Handle	SS201	1
3	Seat	RPTFE	2	10	Ball	SS316	1
2	Cap	WCB/304/316	1	9	Nut	SS201	1
1	Body	WCB/304/316	1	8	Stem	SS316	1
NO Part name Material QTY				NO Part name Material QTY			
				笔 筭 疏 踪 } mm 1:1 ø637ø			
				名称 2PC Ball Valve 青島英利機械有限公司 QINGDAO YINGLI MACHINERY CO., LTD			
笔 筭 疏 踪 } 徑 彈 2 2 2 2							