



in	DN	D2	B	A	D1	L1 _{min}	L2 _{min}	D	R	R1	kg
1/8	6	22	14	21	8.73	6.7	10	8.2	2	0.5	0.18
1/4	8	25	15	25	11.35	10.2	13	10.5	2	0.5	0.20
3/8	10	33	17	28	14.79	10.8	14.5	14.2	2	0.5	0.30
1/2	15	38	18	33	18.32	13.6	18	17.6	3	1.0	0.45
3/4	20	46	19	38	23.66	13.9	19	22.8	3	1.0	0.70
1	25	56	22	44	29.69	17.3	22	28.7	3.5	1.0	1.21
1 1/4	32	62	26	51	38.45	18.0	23	37.3	3.5	1.5	1.47
1 1/2	40	75	30	60	44.52	18.4	24	43.4	4	1.5	2.60
2	50	84	32	64	56.55	19.2	25	55.3	5	1.5	3.05
2 1/2	65	102	45	83	67.61	28.9	34	66.1	5	2.0	5.80
3	80	121	45	95	83.52	30.5	35	81.9	6	2.0	8.85
4	100	152	52	114	108.89	33.0	38	107.1	6	2.0	13.5



				90° Elbow	GB/T14383-2008 ASME B16.11-2016	
					3000 Lb	
				1/8" - 4"	Material: SS316	