



in	DN	Di	B _{min}	A _{min}	d	d ₀	L _{1 min}	L _{min}	C _{min}	G _{min}	kg
1/8	6	9.98	6.4	10	8.2	8.73	6.7	10	11	3	0.01
1/4	8	13.25	8.1	11	10.5	11.35	10.2	13	16	3	0.01
3/8	10	16.67	9.1	13	14.2	14.79	10.8	14.5	18	4	0.02
1/2	15	20.71	10.9	14	17.6	18.32	13.6	18	22	5	0.03
3/4	20	26.03	12.7	16	22.8	23.66	13.9	19	27	6	0.04
1	25	32.59	14.7	19	28.7	29.69	17.3	22	36	6	0.07
1 1/4	32	41.31	17.0	21	37.3	38.45	18.0	23	46	7	0.12
1 1/2	40	47.38	17.8	21	43.4	44.52	18.4	24	50	8	0.14
2	50	59.40	19.0	22	55.3	56.55	19.2	25	65	9	0.22
2 1/2	65	71.61	23.6	27	66.1	67.61	28.9	34	75	10	0.36
3	80	87.39	25.9	28	81.9	83.52	30.5	35	90	10	0.46
4	100	112.63	27.7	32	107.1	108.89	33.0	38	115	13	0.78



		Hex head bushing		ASME B16.11-2016 GB/T14383-2008	
				3000Lb 6000Lb	
		1/8" - 4"		Material: SS316	