



in	DN	W <sub>min</sub>	C <sub>min</sub>	B <sub>min</sub>	D <sub>1</sub>	L <sub>1 min</sub>	L <sub>min</sub>	R	kg
1/8	6	16	7	6	9.98	6.4	10	0.5	0.01
1/4	8	17	10	6	13.25	8.1	11	0.5	0.02
3/8	10	21	11	8	16.67	9.1	13	0.5	0.03
1/2	15	24	14	10	20.71	10.9	14	1	0.06
3/4	20	27	16	11	26.03	12.7	16	1	0.10
1	25	32	21	13	32.59	14.7	19	1	0.18
1 1/4	32	35	24	14	41.31	17.0	21	1.5	0.30
1 1/2	40	37	28	16	47.38	17.8	21	1.5	0.41
2	50	40	32	18	59.40	19.0	22	1.5	0.67
2 1/2	65	46	36	19	71.61	23.6	27	2	1.11
3	80	49	41	21	87.39	25.9	28	2	1.69
4	100	57	65	25	112.63	27.7	32	2	3.48

**PTV**<sup>®</sup>  
Solutions

			Square head plug	ASME B16.11-2016 GB/T14383-2008
				3000Lb 6000Lb
			1/8" - 4"	Material: A105