



in	DN	D	W	D <sub>1</sub>	L <sub>1 min</sub>	L <sub>2 min</sub>	G <sub>min</sub>	R	kg
1/8	6	16	19	8.73	6.7	10	4.8	0.5	0.03
1/4	8	19	25	11.35	10.2	13	4.8	0.5	0.05
3/8	10	22	25	14.79	10.8	14.5	4.8	0.5	0.07
1/2	15	28	32	18.32	13.6	18	6.4	1.0	0.14
3/4	20	35	37	23.66	13.9	19	6.4	1.0	0.24
1	25	44	41	29.69	17.3	22	9.7	1.0	0.41
1 1/4	32	57	44	38.45	18.0	23	9.7	1.5	0.71
1 1/2	40	64	44	44.52	18.4	24	11.2	1.5	0.88
2	50	76	48	56.55	19.2	25	12.7	1.5	1.25
2 1/2	65	92	60	67.61	28.9	34	15.7	2.0	2.20
3	80	108	65	83.52	30.5	35	19.0	2.0	3.20
4	100	140	68	108.89	33.0	38	22.4	2.0	5.65

**PTV**<sup>®</sup>  
Solutions

			Cap	GB/T14383-2008 ASME B16.11-2016
				3000 Lb
			1/8" - 4"	Material: A105