Taiwan
406, 5F-1, No.936,
Wen-Sin Road, Sec 4,
Taichung City, Taiwan
Tel: +886(4)2231 0059
Fax:+886(4)2236 0236

Shanghai
Room 1803, No. 678,
Gu-Bei Road,
Shanghai, China
Tel:+86(21)6295 6805
Fax:+86(21)62956809

DIE ERSTE INDUSTRY CO., LTD.
www.die-erste.com

Technical Data

*Size: DN50(1.5")-DN300(12")
*Nominal Pressure:PN10/PN16
*Working Temperature:-45ºC--+200ºC
*Suitable Mediums: Fresh water, Sewage,
*Sea water, Air, Oils, Acids, Alkalis, Salts, etc

Operation

*Generally, DN50(1.5")-DN300(12") with lever operator.
*All of DN50(1.5")-DN300(12") also can be with electric operator & pneumatic according to the clients' requirements.

Standard

*Design & Manufacture acc.to API 609,MSS SP-67 BS5155, BS EN593..
*Face to Face acc.to DIN3202,API609,MSS SP-67,BS5155, BS EN558,ISO5752.
*Top Flange acc.to ISO5211.
*Pressure test acc.to API598,BS EN12266-1,DIN3230,BS5155.
*Side Flange acc.to DIN2501,ANSI125/150,AS2129,BS4504, BS10D&E,JIS10K.


Part Name & Its Code


No.	Part Name	No.	Part Name
1	Body	9	Washer
2	Seat	10	Half washer
3	Disc	11	Spring circlip
4	Stem	12	Lever
5,7,8	Bushing	13	Gear box
6	"O" Ring		





Part Name & Material

*Body C.I/D.I/carbon steel/stainless steel/Al-Bronze
*Disc :Nickel-plated DI/ stainless steel/Al-Bronze/nickel copper alloy/DI+epoxy coated/PTFE coated/nylon coated/rubber coated
*Seat: rubber(refer to the sheet of seat materials)
*Stem: stainless steel
*Bushing: glass backed PTFE/luberized bronze
*"O" Ring: NBR/EPDM/viton
*Washer: stainless steel/carbon steel
*Half washer: bearing steel
*Spring circlip: stainless steel/ carbon steel
*Lever: malleable cast iron/aluminum/carbon steel
*Gear box: cast Iron/ aluminum









SIZE	A	B	C	D	L	E	Top flange	ϕ	F	S	L0	A1	B1	C1	E1	F1	G1	ϕ1
DN50	140	80	42.3	56	32	90	F07	12.6	10	9	266.7	45	128	105	36	28	226	150
DN65	152	89	45.8	67.87	32	90	F07	12.6	10	9	266.7	45	128	105	36	28	226	150
DN80	159	95	45.8	80.5	32	90	F07	12.6	10	9	266.7	45	128	105	36	28	226	150
DN100	178	114	52	106.3	32	90	F07	15.77	12	11	266.7	45	128	105	36	28	226	150
DN125	191	127	55	131.2	32	90	F07	18.92	14	14	266.7	45	128	105	36	28	226	150
DN150	204	139	55	153.5	32	90	F07	18.92	14	14	266.7	45	128	105	36	28	226	150
DN200	238	175	61	205.08	45	125	F10	22.1	17	17	359	63	179	152	46	34	313	300
DN250	270	203	67.2	255.4	45	125	F10	28.45	22	22	359	63	179	152	46	34	313	300
DN300	315	242	77	306.6	45	125	F10	31.8	24	22	505	78	200	164	46	36	307	300

Note:
*In order to keep the policy of "continual improvement of product", we are entitled to keep improvement in design, material quality, size and specifications etc. Forgive for no further notice.

JYL®

PNEUMATIC ACTUATOR
Serie JYL-AP



Higher performance and reliability

Fully compliance with all the latest international standards

Wide range options in technical specification and highly cost-effective

Compact housing design, suitable for any application and workin genvironment

DESIGN AND CONSTRUCTION

DESIGN

JYL series pneumatic actuators ha ve introduc ed improvement design for rack and pinion. It is alw ays Vtork's mission to o ffer initiative products by c ombining the long field experienc es in products a pplication and the latest production and materials te chnology a v a il a ble in the market tod ay. The benefit of new design has long been verified in practic e. With new te chnicalfe atures equipped, Vtork series pneumatic actuators have advanta geous characteristic in:

- Reliability
- High performance
- Fully compliance with all the latest international standards
- Extensive products range allows best versatility at lower price
- Innovations and patented solutions for a universal drive shaft
- Multifunction position indicator
- Compact and light

CONSTRUCTION

1. A single compact design utilizing identical body and end caps for both double acting and spring return models. This feature reduces inventory and allows field conversion, by adding or removing modular spring cartridges.

2. Full conformance to following latest specifications: ISO 5211, DIN 3337 and VDI/VDE 3845 for product interchangeability and easy mounting of solenoids, limit switches and other accessories.

3. JYL piston rack and pinion design for compact construction, symmetric mounting position, high-cycle life and fast operation. Reverse rotation can be accomplished in the field by simply inverting the pistons.


4. Two independent external travel stop adjustments permit easy and precise adjustment of +/- 5° in both directions. This adjustment may be made in either the open or closed position and provides for accurate valve alignment.

5. Multiple bearings and guides on pistons and racks for precise operation, low friction, high cycle life and a blowout proof pinion shaft.

6. Electroless nickel-plated blowout resistant, bearing guided, one-piece pinion shaft for improved safety and maximum cycle life.

7. High precision teeth on piston racks and pinion shaft for accurate positioning, low backlash, and maximum engagement resulting in overall efficient operation.

8. Extruded aluminum body with both internal and external corrosion protections having a honed cylinder surface for longer life and a lower coefficient of friction.



9. Modular preloaded spring cartridges designed with coated springs for simple range versatility, greater safety and corrosion resistance.

10. Selected high quality bearings and seals that provide a wide operating temperature range, low friction, and high cycle life.

11. Internal and external stainless steel fasteners for long term corrosion resistance.

12. Multifunctional position indicator for visual position indication, and a direct, easy, economical way to mount popular sensors.

RANGE OF OPTIONS, QUALITY MANUFACTURING, AND ACCESSORIES

RANGE OF OPTIONS

A. Stainless steel 304 or 316 drive shafts are available on request for all sizes no matter the type of corrosion protection selected.
B. For extremely high or low temperature applications, all models may be equipped with FPM or Silicon O rings along with an JYL tested and certified suitable lubricant.
C. Other than the standard double square bottom drive shaft connection, we can supply a keyed drive connection, a flat head connection or a special personalized drive connection.


QUALITY MANAGEMENT

- Production conforms to ISO9001.
- Each individual actuator has been factory inspe cted and tested and given a serial number for full trac e ability.
- Each individual actuator is individually packed in a special cardboard carton for protection,with a product description label for easy identification and includes installation,operation and maintenance instructions .

ACCESSORIES AVAILABLE

- Different Square reductions suitable for drive shaft
- Centering rings for all sizes
- Brackets
- Couplings
- Solenoid valves
- Switch boxes
- Proximity switches
- Gear boxes
- Positioners

Parts And Materials



Item Number	Part Description	Material Quality	QTY	Item Number	Part Description	Material Quality	QTY	Item Number	Part Description	Material Quality	QTY
1	Body	Aluminium alloy	1	12	Nut(stop screw)	Stainless steel	2	23	Bearing(pinion top)	POM+PTFE	1
2	Left End cap	Aluminium alloy	1	13	Washer (stop screw)	Stainless steel	2	24	Bearing(pinion head)	POM+PTFE	2
3	Drive shaft	Alloy Steel	1	14	Spring clip	Spring steel	1	25	Bearing(pinion bottom)	POM+PTFE	1
4	Right end cap	Aluminium alloy	1	15	Position indicator	Nylon	1	26	Wear band	Nylon	2
5	OCTI-CAM	Alloy Steel	1	16	Indicator thrust bearing	Stainless steel	1	27	Spring seat	Nylon	24
6	Thrust bearing (pinion top)	POM+PTFE	1	17	Cap screw	Stainless steel	1	28	Spring	High-carbon steel	12
7	Thrust bearing	POM+PTFE	1	18	Color code	Nylon	2	29	Straining beam	Copper pipe	12
8	Thrust washer	Stainless steel	1	19	"o" ring(stop screw)	NBR	2	30	Plug	NBR	2
9	Piston	Aluminium alloy	2	20	"o" ring(piston)	NBR	2	31	"o" ring(end cap)	NBR	2
10	Cap screw (end cap)	Stainless steel	8	21	"o" ring(pinion bottom)	NBR	1				
11	Stop top screw	Stainless steel	2	22	"o" ring(pinion top)	NBR	1				

TECHNICAL DATA(METRIC UNIT)

Model TypeA	AP032		AP050		AP065		AP0075		AP085		AP095		AP110		AP125		AP140		AP160		AP190		AP210		AP240		AP270		AP300		AP350		AP400	
	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S	D	S
Diameter mm	32		50		65		75		85		95		110		125		140		160		190		210		240		270		300		350		400	
Air Volume Opening(L)	0.03		0.09		0.19		0.30		0.44		0.88		0.83		1.41		1.76		2.85		4.75		6.60		11.40		15.80		19.09		27.65		42.81	
Air Volume Closing(L)	0.04		0.15		0.32		0.50		0.66		1.17		1.27		2.13		2.72		4.08		7.20		10.29		15.10		18.80		28.23		44.10		62.05	
Opening Time (sec)	0.3		0.3	0.9	0.4	0.9	0.4	0.9	0.9	1.0	0.9	1.4	0.9	1.4	1.3	2.4	1.3	2.8	2.0	4.8	2.2	2.4	2.9	3.4	3.2	3.8	4.4	5.0	5.0	6.0	6.2	7.4	7.5	9.6
closing Time (sec)	0.4		0.4	0.7	0.4	0.8	0.4	0.9	0.9	1.2	1.0	1.4	1.0	1.6	1.4	2.4	1.4	3.0	2.4	4.9	2.6	3.0	3.8	4.1	3.7	4.0	4.9	5.5	6.0	6.8	7.2	8.4	8.5	10.6
Weight (Kg)hai	0.47	0.59	1.13	1.25	1.97	2.21	2.93	3.29	3.78	4.26	5.14	5.86	6.09	7.17	10.86	12.54	13.77	15.93	20.15	23.75	28.41	33.81	40.03	48.43	52.6	77.76	73.64	90.6	108	135.6	146.7	188.1	220.5	283.5

1. For model 32-160

(1)Room temperature (2)Actuator stroke 90° (3) Solenoid valve with orifice of 4 mm and a flow capacity Qn400L/min (4) Inside pipe diameter 6 mm (5) Medium clean air

(6) Air supply pressure 5.5 bar (7)Actuator without external resistance load

2. For model 190-400

(1)Room temperature (2)Actuator stroke 90° (3)Solenoid valve with orifice of 12 mm and a flow capacity Qn5100L/min (4) Inside pipe diameter 8 mm (5) Medium clean air


(6) Air supply pressure 5.5 bar (7)Actuator without external resistance load


Cautions: obviously on the field applications when one or more of the above parameter are different, the moving time will be di fferent

Air consumption rest with air supply, air volume and action cycle times. Expressions:

$$L/min = \text{Air volume(opening air volume+closing air volume)} X \left[\frac{\text{Air Supply(Kpa)+101.3}}{101.3} \right] X \text{Action times(/min)}$$

METRIC TORQUE RATINGS





DOUBLE ACTING TORQUE RATINGS IN Nm

Model	Supply Pressure (Unit:bar)									
	2.5	**3**	**3.5**	**4**	**4.5**	**5**	**5.5**	**6**	**7**	**8**
AP032	2.9	3.4	4.0	4.6	5.3	5.9	6.5	7.1	8.3	9.5
AP050	8.6	10.4	12.3	14.2	16.0	17.9	19.8	21.6	25.4	29.1
AP065	17.4	21.2	25.0	28.7	32.5	36.3	40.1	43.9	51.4	59.0
AP075	27.0	32.9	38.8	44.7	50.5	56.4	62.3	68.2	79.9	91.7
AP085	39.7	48.3	56.9	65.6	74.2	82.8	91.4	100.1	117.3	134.6
AP095	55.7	67.9	80.0	92.1	104.2	116.4	128.5	140.6	164.8	189.1
AP110	72.0	89.3	105.0	120.6	136.3	152.0	167.6	183.3	214.6	245.9
AP125	128.7	159.5	187.5	215.4	243.4	271.4	299.4	327.4	383.3	439.3
AP140	196	237	278	319	360	401	442	483	565	647
AP160	263.5	326.6	383.9	441.2	498.5	555.8	613.1	670.4	785.0	899.7
AP190	428.5	518.0	607.3	696.6	785.9	875.3	964.6	1053.9	1232.5	1411.1
AP210	598.2	723.2	847.9	972.6	1097.3	1222.0	1346.6	1471.3	1720.7	1970.1
AP240	928.3	1122.0	1315.0	1508.0	1702.0	1895.0	2089.0	2282.0	2669.0	3056.0
AP270	1305.0	1577.0	1849.0	2121.0	2393.0	2665.0	2937.0	3209.0	3753.0	4297.0
AP300	1678.6	2029.4	2379.3	2729.2	3079.1	3429.0	3778.9	4128.8	4828.5	5528.3
AP350	2492.5	3011.8	3531.1	4050.4	4569.6	5088.9	5608.2	6127.5	7166.0	8204.6
AP400	3798.1	4589.4	5380.7	6172.0	6963.3	7754.5	8545.8	9337.1	10919.7	12502.2

SINGLE ACTING TORQUE RATINGS IN Nm

Model	Supply Pressure (Unit:bar)																				Spring stroke	
	2.5		**3**		**3.5**		**4**		**4.5**		**5**		**5.5**		**6**		**7**		**8**			
	0°	**90°**	**0°**	**90°**	**0°**	**90°**	**0°**	**90°**	**0°**	**90°**	**0°**	**90°**	**0°**	**90°**	**0°**	**90°**	**0°**	**90°**	**0°**	**90°**	**90°**	**0°**
AP050 S05	**5.1**	**3.4**	6.9	5.3	8.8	7.2	10.7	9.0	12.5	10.9	14.4	12.8	16.3	14.6	18.1	16.5	21.9	20.2	25.6	23.9	**5.2**	**3.5**
AP050 S06	4.4	2.4	**6.2**	**4.3**	8.1	6.1	10.0	8.0	11.8	9.9	13.7	11.7	15.6	13.6	17.4	15.5	21.2	19.2	24.9	22.9	**6.2**	**4.2**
AP050 S07			5.5	3.2	**7.4**	**5.1**	9.3	7.0	11.1	8.8	13.0	10.7	14.9	12.6	16.7	14.4	20.5	18.2	24.2	21.9	**7.2**	**4.9**
AP050 S08					6.7	4.1	**8.6**	**5.9**	10.4	7.8	12.3	9.7	14.2	11.5	16.0	13.4	19.8	17.1	23.5	20.9	**8.2**	**5.6**
AP050 S09							7.9	4.9	**9.7**	**6.8**	11.6	8.6	13.5	10.5	15.3	12.4	19.1	16.1	22.8	19.8	**9.3**	**6.3**
AP050 S10									9.0	5.7	**10.9**	**7.6**	12.8	9.5	14.6	11.3	18.4	15.1	22.1	18.8	**10.3**	**7.0**
AP050 S11											10.2	6.6	**12.1**	**8.4**	13.9	10.3	17.7	14.0	21.4	17.8	**11.3**	**7.7**
AP050 S12													11.4	7.4	**13.2**	**9.3**	17.0	13.0	20.7	16.7	**12.4**	**8.4**
AP065 S05	**8.7**	**4.3**	12.5	8.1	16.3	11.9	20.0	15.6	23.8	19.4	27.6	23.2	31.4	27.0	35.2	30.8	42.7	38.3	50.3	45.9	**13.1**	**8.7**
AP065 S06	7.0	1.7	**10.7**	**5.5**	14.5	9.2	18.3	13.0	22.1	16.8	25.9	20.6	29.7	24.4	33.4	28.2	41.0	35.7	48.6	43.3	**15.7**	**10.4**
AP065 S07			9.0	2.8	**12.8**	**6.6**	16.6	10.4	20.4	14.2	24.1	18.0	27.9	21.8	31.7	25.5	39.3	33.1	46.8	40.7	**18.3**	**12.2**
AP065 S08					11.0	4.0	**14.8**	**7.8**	18.6	11.6	22.4	15.4	26.2	19.1	30.0	22.9	37.5	30.5	45.1	38.1	**21.0**	**13.9**
AP065 S09							13.1	5.2	**16.9**	**9.0**	20.7	12.7	24.4	16.5	28.2	20.3	35.8	27.9	43.4	35.4	**23.6**	**15.7**
AP065 S10									15.1	6.3	**18.9**	**10.1**	22.7	13.9	26.5	17.7	34.0	25.2	41.6	32.8	**26.2**	**17.4**
AP065 S11											17.2	7.5	**21.0**	**11.3**	24.7	15.1	32.3	22.6	39.9	30.2	**28.8**	**19.1**
AP065 S12													19.2	8.7	**23.0**	**12.4**	30.6	20.0	38.1	27.6	**31.4**	**20.9**
AP075 S05	**16.3**	**10.2**	22.2	16.0	28.1	21.9	34.0	27.8	39.8	33.7	45.7	39.6	51.6	45.4	57.5	51.3	69.2	63.1	81.0	74.8	**16.9**	**10.7**
AP075 S06	14.2	6.8	**20.1**	**12.7**	25.9	18.6	31.8	24.4	37.7	30.3	43.6	36.2	49.4	42.1	55.3	47.9	67.1	59.7	78.8	71.4	**20.2**	**12.8**
AP075 S07			17.9	9.3	**23.8**	**15.2**	29.7	21.1	35.6	26.9	41.4	32.8	47.3	38.7	53.2	44.6	64.9	56.3	76.7	68.1	**23.6**	**15.0**
AP075 S08					21.7	11.8	**27.5**	**17.7**	33.4	23.6	39.3	29.4	45.2	35.3	51.0	41.2	62.8	53.0	74.5	64.7	**27.0**	**17.1**
AP075 S09							25.4	14.3	**31.3**	**20.2**	37.1	26.1	43.0	32.0	48.9	37.8	60.7	49.6	72.4	61.3	**30.3**	**19.3**
AP075 S10									29.1	16.8	**35.0**	**22.7**	40.9	28.6	46.8	34.5	58.5	46.2	70.3	58.0	**33.7**	**21.4**
AP075 S11											32.9	19.3	**38.7**	**25.2**	44.6	31.1	56.4	42.8	68.1	54.6	**37.1**	**23.5**
AP075 S12													36.6	21.8	**42.5**	**27.7**	54.2	39.5	66.0	51.2	**40.4**	**25.7**
AP085 S05	**23.2**	**13.7**	31.8	22.3	40.4	30.9	49.0	39.5	57.6	48.1	66.3	56.8	74.9	65.4	83.5	74.0	100.8	91.3	118.0	108.5	**26.1**	**16.6**
AP085 S06	19.8	8.4	**28.4**	**17.0**	37.1	25.7	45.7	34.3	54.3	42.9	62.9	51.5	71.6	60.2	80.2	68.8	97.4	86.0	114.7	103.3	**31.3**	**19.9**
AP085 S07			25.1	11.8	**33.8**	**20.5**	42.4	29.1	51.0	37.7	59.6	46.3	68.3	55.0	76.9	63.6	94.1	80.8	111.4	98.1	**36.5**	**23.2**
AP085 S08					30.4	15.2	**39.1**	**23.9**	47.7	32.5	56.3	41.1	64.9	49.7	73.6	58.4	90.8	75.6	108.1	92.9	**41.7**	**26.5**
AP085 S09							35.8	18.7	**44.4**	**27.3**	53.0	35.9	61.6	44.5	70.3	53.2	87.5	70.4	104.8	87.7	**46.9**	**29.8**
AP085 S10									41.1	22.1	**49.7**	**30.7**	58.3	39.3	67.0	48.0	84.2	65.2	101.5	82.5	**52.1**	**33.1**
AP085 S11											46.4	25.5	**55.0**	**34.1**	63.6	42.7	80.9	60.0	98.1	77.2	**57.3**	**36.4**
AP085 S12													51.7	28.9	**60.3**	**37.5**	77.6	54.8	94.8	72.0	**62.5**	**39.7**
AP095 S05	**33.6**	**20.9**	45.8	33.0	57.9	45.1	70.0	57.3	82.1	69.4	94.3	81.5	106.4	93.6	118.5	105.8	142.7	130.0	167.0	154.2	**34.9**	**22.1**
AP095 S06	29.2	13.9	**41.4**	**26.1**	53.5	38.2	65.6	50.3	77.7	62.4	89.8	74.5	102.0	86.7	114.1	98.8	138.3	123.0	162.6	147.3	**41.8**	**26.5**
AP095 S07			36.9	19.1	**49.1**	**31.2**	61.2	43.3	73.3	55.4	85.4	67.6	97.5	79.7	109.7	91.8	133.9	116.1	158.1	140.3	**48.8**	**30.9**
AP095 S08					44.6	24.2	**56.8**	**36.4**	68.9	48.5	81.0	60.6	93.1	72.7	105.2	84.8	129.5	109.1	153.7	133.3	**55.8**	**35.4**
AP095 S09							52.3	29.4	**64.5**	**41.5**	76.6	53.6	88.7	65.8	100.8	77.9	125.1	102.1	149.3	126.4	**62.7**	**39.8**
AP095 S10									60.0	34.5	**72.2**	**46.7**	84.3	58.8	96.4	70.9	120.6	95.1	144.9	119.4	**69.7**	**44.2**
AP095 S11											67.7	39.7	**79.9**	**51.8**	92.0	63.9	116.2	88.2	140.5	112.4	**76.7**	**48.6**
AP095 S12													75.4	44.8	**87.6**	**57.0**	111.8	81.2	136.0	105.4	**83.6**	**53.0**
AP110 S05	**43.4**	**26.2**	60.7	43.4	76.4	59.1	92.0	74.8	107.7	90.4	123.4	106.1	139.0	121.8	154.7	137.4	186.0	168.8	217.3	200.1	**45.9**	**28.6**
AP110 S06	37.7	17.0	**55.0**	**34.3**	70.6	49.9	86.3	65.6	102.0	81.3	117.6	96.9	133.3	112.6	149.0	128.3	180.3	159.6	211.6	190.9	**55.0**	**34.3**
AP110 S07			49.3	25.1	**64.9**	**40.8**	80.6	56.4	96.2	72.1	111.9	87.8	127.6	103.4	143.2	119.1	174.6	150.4	205.9	181.8	**64.2**	**40.0**
AP110 S08					59.2	31.6	**74.9**	**47.3**	90.5	62.9	106.2	78.6	121.9	94.3	137.5	109.9	168.9	141.3	200.2	172.6	**73.4**	**45.8**
AP110 S09							69.1	38.1	**84.8**	**53.8**	100.5	69.4	116.1	85.1	131.8	100.8	163.1	132.1	194.5	163.4	**82.5**	**51.5**
AP110 S10									79.1	44.6	**94.8**	**60.3**	110.4	75.9	126.1	91.6	157.4	122.9	188.7	154.2	**91.7**	**57.2**
AP110 S11											89.0	51.1	**104.7**	**66.7**	120.4	82.4	151.7	113.7	183.0	145.1	**100.9**	**62.9**
AP110 S12													99.0	57.6	**114.6**	**73.2**	146.0	104.6	177.3	135.9	**110.0**	**68.6**

METRIC TORQUE RATINGS


JYL®

SINGLE ACTING TORQUE RATINGS IN Nm


Model	Supply Pressure (Unit: bar)																				Spring stroke	
	2.5		3		3.5		4		4.5		5		5.5		6		7		8			
	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	90°	0°
AP125 S05	**77.7**	**48.2**	108.5	78.9	136.5	106.9	164.4	134.9	192.4	162.9	220.4	190.9	248.4	218.4	276.4	246.8	332.3	302.8	388.3	358.7	80.6	51.0
AP125 S06	67.5	32.0	**98.3**	**62.8**	126.3	90.8	154.2	118.8	182.2	146.8	210.2	174.7	238.2	202.7	266.2	230.7	322.1	286.7	378.1	342.6	96.7	61.2
AP125 S07			88.1	46.7	**116.1**	**74.7**	144.0	102.7	172.0	130.7	200.0	158.6	228.0	186.6	256.0	214.6	311.9	270.6	367.9	326.5	112.8	71.4
AP125 S08					105.9	58.6	**133.8**	**86.6**	161.8	114.5	189.8	142.5	217.8	170.5	245.8	198.5	301.7	254.4	357.7	310.4	128.9	81.6
AP125 S09							123.6	70.5	**151.6**	**98.4**	179.6	126.4	207.6	154.4	235.6	182.4	291.5	238.3	347.5	294.3	145.0	91.8
AP125 S10									141.4	82.3	169.4	110.3	197.4	138.3	225.4	166.3	281.3	222.2	337.3	278.2	161.1	102.0
AP125 S11											159.2	94.2	187.2	122.2	215.2	150.2	271.1	206.1	327.1	262.1	177.2	112.2
AP125 S12													177.0	106.1	205.0	134.0	260.9	190.0	316.9	246.0	193.3	122.4
AP140 S05	114.2	74.1	155.1	115	196.1	156	237.0	196.9	277.9	237.8	318.8	278.7									122.4	82.3
AP140 S06	97.7	49.6	138.7	90.6	179.6	131.5	220.5	172.4	261.5	213.3	302.4	254.3	343.3	295.2							146.8	98.7
AP140 S07			122.2	66.1	163.2	107.0	204.1	147.9	245.0	188.9	285.9	229.8	326.9	270.7	367.8	311.6					171.3	115.2
AP140 S08					146.7	82.5	187.6	123.5	228.6	164.4	269.5	205.3	310.4	246.2	351.3	287.2	433.2	369.0			195.8	131.6
AP140 S09							171.2	99.0	212.1	139.9	253.0	180.9	294.0	221.8	334.9	262.7	416.7	344.6	498.6	426.4	220.2	148.1
AP140 S10									195.7	115.5	236.6	156.4	277.5	197.3	318.4	238.2	400.3	320.1	482.1	401.9	244.7	164.5
AP140 S11											220.1	131.9	261.1	172.8	302.0	213.8	383.8	295.6	465.7	377.5	269.2	181.0
AP140 S12													244.6	148.4	285.5	189.3	367.4	271.1	449.2	353.0	293.6	197.4
AP160 S05	**153.5**	**101.3**	216.6	164.4	273.9	221.7	331.2	279.0	388.5	336.3	445.8	393.6	503.1	450.9	560.4	508.2	675.0	622.8	789.7	737.4	162.3	110.0
AP160 S06	131.5	68.8	**194.6**	**131.9**	251.9	189.2	309.2	246.5	366.5	303.8	423.8	361.1	481.1	418.4	538.4	475.7	653.0	590.3	767.7	705.0	194.7	132.0
AP160 S07			172.6	99.5	**229.9**	**156.8**	287.2	214.1	344.5	271.4	401.8	328.7	459.1	386.0	516.4	443.3	631.0	557.9	745.7	672.5	227.2	154.0
AP160 S08					207.9	124.3	**265.2**	**181.6**	322.5	238.9	379.8	296.2	437.1	353.5	494.4	410.8	609.0	525.4	723.7	640.1	259.6	176.0
AP160 S09							243.2	149.2	**300.5**	**206.5**	357.8	263.8	415.1	321.1	472.4	378.4	587.0	493.0	701.7	607.6	292.1	198.0
AP160 S10									278.5	174.0	335.8	231.3	393.1	288.6	450.4	345.9	565.0	460.5	679.7	575.2	324.5	220.0
AP160 S11											313.8	198.9	371.1	256.2	428.4	313.5	543.0	428.1	657.7	542.7	357.0	242.0
AP160 S12													349.1	223.7	406.4	281.0	521.0	395.6	635.7	510.3	389.4	264.0
AP190 S05	246.8	167.4	336.3	256.9	425.6	346.2	514.9	435.5	604.2	524.8	693.5	614.1									261.2	181.8
AP190 S06	210.4	115.1	299.9	204.6	389.2	293.9	478.5	383.3	567.8	472.6	657.2	561.9	746.5	651.2							313.4	218.1
AP190 S07			263.6	152.4	352.9	241.7	442.2	331.0	531.5	420.3	620.8	509.6	710.1	599.0	799.4	688.3					365.6	254.5
AP190 S08					316.5	189.5	405.8	278.7	495.1	368.1	584.5	457.4	673.8	546.7	779.5	636.0	941.7	814.7			417.8	290.8
AP190 S09							369.5	226.6	458.8	315.9	548.1	405.2	637.4	494.5	745.2	583.8	905.3	762.4	1084.0	941.1	470.1	327.2
AP190 S10									422.4	263.6	511.8	353.0	601.1	442.3	710.9	531.6	869.0	710.2	1047.6	888.8	522.3	363.5
AP190 S11											475.4	300.7	564.7	390.0	676.6	479.3	832.6	658.0	1011.3	836.6	574.5	399.9
AP190 S12													528.4	337.8	642.3	427.1	796.3	605.7	974.9	784.4	628.8	436.8
AP210 S05	**352.8**	**239.1**	477.8	364.1	602.5	488.8	727.2	613.5	851.9	738.2	976.6	862.9	1101.2	987.5	1225.9	1112.2	1475.3	1361.6	1724.7	1611.0	359.1	245.4
AP210 S06	303.7	167.3	**428.7**	**292.3**	553.4	417.0	678.1	541.7	802.8	666.4	927.5	791.0	1052.2	915.7	1176.9	1040.4	1426.2	1289.8	1675.6	1539.2	430.9	294.5
AP210 S07			379.6	220.5	**504.3**	**345.2**	629.0	469.8	753.7	594.5	878.4	719.2	1003.1	843.9	1127.8	968.6	1377.2	1218.0	1626.5	1467.4	502.7	343.6
AP210 S08					455.3	273.3	**579.9**	**398.0**	704.6	522.7	829.3	647.4	954.0	772.1	1078.7	896.8	1328.1	1146.2	1577.5	1395.5	574.6	392.6
AP210 S09							530.9	326.2	**655.6**	**450.9**	780.2	575.6	904.9	700.3	1029.6	825.0	1279.0	1074.3	1528.4	1323.7	646.4	441.7
AP210 S10									606.5	379.1	731.2	503.8	855.8	628.4	980.5	753.1	1229.9	1002.5	1479.3	1251.9	718.2	490.8
AP210 S11											682.1	431.9	806.8	556.6	931.5	681.3	1180.8	930.7	1430.2	1180.1	790.0	539.9
AP210 S12													757.7	484.8	882.4	609.5	1131.8	858.9	1381.1	1108.3	861.8	589.0
AP240 S05	517.8	374.3	711.2	567.7	904.6	761.1	1098.0	954.5	1291.4	1147.9	1484.8	1341.3									554.0	410.5
AP240 S06	435.7	263.5	629.1	456.9	822.5	650.3	1015.9	843.7	1209.3	1037.1	1402.7	1230.5	1596.1	1423.9							664.8	492.6
AP240 S07			547.0	346.1	740.4	539.5	933.8	732.9	1127.2	926.3	1320.6	1119.7	1514.0	1313.1	1707.4	1506.5					775.6	574.7
AP240 S08					658.3	428.7	851.7	622.1	1045.1	815.5	1238.5	1008.9	1431.9	1202.3	1625.3	1395.7	2012.1	1782.5			886.4	656.8
AP240 S09							769.6	511.3	963.0	704.7	1156.4	898.1	1349.8	1091.5	1543.2	1284.9	1930.0	1671.7	2316.8	2058.5	997.2	738.9
AP240 S10									880.9	593.9	1074.3	787.3	1267.7	980.7	1461.1	1174.1	1847.9	1560.9	2234.7	1947.7	1108.0	821.0
AP240 S11											992.2	676.5	1185.6	869.9	1379.0	1063.3	1765.8	1450.1	2152.6	1836.9	1218.8	903.1
AP240 S12													1103.5	759.1	1296.9	952.5	1683.7	1339.3	2070.5	1726.1	1329.6	985.2
AP270 S05	745.9	**519.4**	1017.9	791.4	1289.9	1063.4	1561.8	1335.3	1833.8	1607.3	2105.7	1879.2									786.0	**559.5**
AP270 S06	634.0	362.2	**906.0**	**634.2**	1178.0	906.2	1449.9	1178.1	1721.9	1450.1	1993.8	1722.0	2265.8	1994.0							943.2	**671.4**
AP270 S07			794.1	477.0	1166.1	**749.0**	1338.0	1020.9	1610.0	1292.9	1881.9	1564.8	2153.9	1836.8	2425.9	2108.8					1100.4	**783.3**
AP270 S08					954.2	591.8	1226.1	**863.7**	1498.1	1135.7	1770.0	1407.6	2042.0	1679.6	2314.0	1951.6	2857.9	2495.5			1257.6	**895.2**
AP270 S09							1114.2	706.5	1386.2	**978.5**	1658.1	1250.4	1930.1	1522.4	2202.1	1794.4	2746.0	2338.3	3289.9	2882.2	1414.8	**1007.1**
AP270 S10									1274.3	821.3	1546.2	**1093.2**	1818.2	1365.2	2090.2	1637.2	2634.1	2181.1	3178.0	2725.0	1572.0	**1119.0**
AP270 S11											1434.3	936.0	1706.3	**1208.0**	1978.3	1480.0	2522.2	2023.9	3066.1	2567.8	1729.2	1230.9
AP270 S12													1594.4	1050.8	1866.4	**1322.8**	2410.3	1866.7	2954.2	2410.6	1886.4	**1342.8**
AP300 S05	**987.5**	**646.7**	1338.3	997.5	1688.2	1347.4	2038.1	1697.3	2388.0	2047.2	2737.9	2397.1	3087.8	2747.0	3437.7	3096.9	4137.4	3796.6	4837.2	4496.4	1031.9	**691.1**
AP300 S06	849.3	440.3	**1200.1**	**791.1**	1550.0	1141.0	1899.9	1490.9	2249.8	1840.8	2599.6	2190.7	2949.5	2540.6	3299.4	2890.5	3999.2	3590.3	4699.0	4290.1	1238.3	**829.3**
AP300 S07			1061.9	584.7	**1411.7**	**934.6**	1761.6	1284.5	2111.5	1634.4	2461.4	1984.3	2811.3	2334.2	3161.2	2684.1	3861.0	3383.9	4560.8	4083.7	1444.7	**967.5**
AP300 S08					1273.5	728.2	**1623.4**	**1078.1**	1973.3	1428.0	2323.2	1777.9	2673.1	2127.8	3023.0	2477.7	3722.8	3177.5	4422.6	3877.3	1651.0	**1105.8**
AP300 S09							1485.2	871.8	**1835.1**	**1221.7**	2185.0	1571.5	2534.9	1921.4	2884.8	2271.3	3584.6	2971.1	4284.4	3670.9	1857.4	**1244.0**
AP300 S10									1696.9	1015.3	2046.8	**1365.2**	2396.7	1715.1	2746.6	2065.0	3446.3	2764.7	4146.1	3464.5	2063.8	**1382.2**
AP300 S11											1908.5	1158.8	2258.4	**1508.7**	2608.3	1858.6	3308.1	2558.4	4007.9	3258.2	2270.2	**1520.4**
AP300 S12													2120.2	1302.3	2470.1	**1652.2**	3169.9	2352.0	3869.7	3051.8	2476.6	**1658.6**
AP350 S05	**1498.2**	**1017.1**	2017.5	1536.4	2536.8	2055.6	3056.1	2574.9	3575.3	3094.2	4094.6	3613.5	4613.9	4132.7	5133.2	4652.0	6171.7	5690.6	7210.3	6729.1	1475.5	**994.3**
AP350 S06			**1818.6**	**1241.3**	2337.9	1760.5	2857.2	2279.8	3376.5	2799.1	3895.8	3318.4	4415.0	3837.7	4934.3	4356.9	5972.9	5395.5	7011.4	6434.0	1770.5	**1193.2**
AP350 S07			1619.8	946.2	**2139.1**	**1465.5**	2658.3	1984.7	3177.6	2504.0	3696.9	3023.3	4216.2	3542.6	4735.5	4061.8	5774.0	5100.4	6812.6	6139.0	2065.6	**1392.0**
AP350 S08					1940.2	1170.4	**2459.5**	**1689.6**	2978.8	2208.9	3498.0	2728.2	4017.3	3247.5	4536.6	3766.8	5575.1	4805.3	6613.7	5843.9	2360.7	**1590.9**
AP350 S09					1741.3	875.3	2260.6	1394.6	**2779.9**	**1913.8**	3299.2	2433.1	3818.5	2952.4	4337.7	3471.7	5376.3	4510.2	6414.8	5548.8	2655.8	**1789.7**
AP350 S10							2061.8	1099.5	2581.0	1618.7	**3100.3**	**2138.0**	3619.6	2657.3	4138.9	3176.6	5177.4	4215.1	6216.0	5253.7	2950.9	**1988.6**
AP350 S11							1862.9	804.4	2382.2	1323.7	2901.5	1842.9	**3420.7**	**2362.2**	3940.0	2881.5	4978.6	3920.0	6017.1	4958.6	3246.0	**2187.5**
AP350 S12									2183.3	1028.6	2702.6	1547.8	3221.9	2067.1	3741.2	**2586.4**	4779.7	3624.9	5818.3	4663.5	3541.1	**2386.3**
AP400 S05	2222.0	1497.0	3013.0	2288.0	3805.0	3080.0	4596.0	3871.0	5387.0	4662.0	6179.0	5454.0									2301.0	1576.0
AP400 S06			2698.0	1828.0	3490.0	2620.0	4281.0	3411.0	5072.0	4202.0	5863.0	4993.0	6655.0	5785.0							2761.0	1891.0
AP400 S07			2383.0	1368.0	3174.0	2195.0	3966.0	2951.0	4757.0	3742.0	5548.0	4533.0	6339.0	5324.0	7131.0	6116.0					3221.0	2206.0
AP400 S08					2859.0	1699.0	3650.0	2490.0	4442.0	3282.0	5233.0	4073.0	6024.0	4864.0	6816.0	5656.0	8398.0	7238.0			3682.0	2522.0
AP400 S09					2544.0	1239.0	3335.0	2030.0	4126.0	2821.0	4918.0	3613.0	5709.0	4404.0	6500.0	5195.0	8083.0	6778.0	9665.0	8360.0	4142.0	2837.0
AP400 S10							3020.0	1570.0	3811.0	2361.0	4603.0	3153.0	5394.0	3944.0	6185.0	4735.0	7768.0	6318.0	9350.0	7900.0	4602.0	3152.0
AP400 S11							2705.0	1110.0	3496.0	1901.0	4287.0	2692.0	5079.0	3484.0	5870.0	4275.0	7452.0	5857.0	9035.0	7440.0	5062.0	3467.0
AP400 S12									3181.0	1441.0	3972.0	2232.0	4763.0	2023.0	5555.0	3815.0	7137.0	5397.0	8720.0	6980.0	5522.0	3782.0

INSTALLATION


FRONT VIEW SIDE VIEW




TOP



AIR CONNECTION



BOTTOM



MODEL	A	B	C	L	E	F	P	ØZ	N	I	FLANGE	Q	Q1	W	W1	Ch	T
AP032	37	47	50	110	27	50	20	40	10	10	F03	—	36	—	M5×9	9×9	G1/8"
AP050	45	70.5	70	154	41.5	80	20	40	10	12	F03/05	36	50	M5×7.5	M6×9	11×11	G1/4"
AP065	62	89.5	89	189	51.5	80	20	40	10	16	F05/07	50	70	M6×9	M8×12	14×14	G1/4"
AP075	68	102.5	100	210	59	80	20	40	14	16	F05/07	50	70	M6×9	M8×12	14×14	G1/4"
AP085	68	112.5	113	229	63.5	80	20	40	14	19	F05/07	50	70	M6×9	M8×12	17×17	G1/4"
AP095	92	126	123	264	71	80	20	40	14	19	F05/07	50	70	M6×9	M8×12	17×17	G1/4"
AP110	93	138.5	136	266	76.5	80	20	40	14	19	F07/10	70	102	M8×12	M10×15	17×17	G1/4"
AP125	96	157	161	337	85	80	30	56	22	25	F07/10	70	102	M8×12	M10×15	22×22	G1/4"
AP140	110	178	178	377	97	80	30	56	22	31	F10/12	102	125	M10×15	M12×18	27×27	G1/4"
AP160	112	196	200	412	106	130	30	56	22	31	F10/12	102	125	M10×15	M12×18	27×27	G1/4"
AP190	136	216.5	232	488	112	130	30	56	22	41	F10/14	102	140	M10×15	M16×24	36×36	G1/4"
AP210	140	235.5	255	550	120	130	30	80	32	40	F14	—	140	—	M16×24	36×36	G1/4"
AP240	159	262	292	602	131	130	30	80	32	50	F16	—	165	—	M20×28	46×46	G1/2"
AP270	159	295	331	672	147.5	130	30	80	32	50	F16	—	165	—	M20×28	46×46	G1/2"
AP300	180	335	354	784	173	130	30	80	32	50	F16	—	165	—	M20×28	46×46	G1/2"
AP350	270	385	410	845	195	130	30	80	32	50	F16/F25	165	254	M20×28	M16×30	46×46	G1/2"
AP400	290	520	466	956	260	130	30	80	32	60	F25	—	254	—	M16×30	55×55	G1/2"

MODEL SELECTION

MODEL	TYPE	SPRING QTY	FLANGE	SQURE	OPTION	SEALING PART
AP032	D=DOUBLE ACTING S=SPRING RETURN		F03	9×9	CAP COLOR RAL 7046 9004 5021 3020 6002 5015 TYPE OF BODY P Smooth Surface + hard Anodized S Sandblasted Surface + hard Anodized (Color: Grey) H Sandblasted Surface + hard Anodized (Color: Dark Grey) F Sandblasted Surface + hard Anodized + PTFE Coated	STANDARD NITRILE RUBBER -15°C-+80°C HT FLUORORUBBER (FOR HIGH TEMPERATURE) -15°C-+150°C LT SILASTIC (FOR LOW TEMPERATURE) -40°C-+80°C
AP050		ONLY FOR SPRING REST 4 5 6 7 8 9 10 11 12	F03/05	11×11		
AP065			F05/07	14×14		
AP075			F05/07	14×14		
AP085			F05/07	17×17		
AP095			F05/07	17×17		
AP110			F07/10	17×17		
AP125			F07/10	22×22		
AP140			F10/12	27×27		
AP160			F10/12	27×27		
AP190			F10/14	36×36		
AP210			F14	36×36		
AP240			F16	46×46		
AP270			F16	46×46		
AP300			F16	46×46		
AP350			F16/25	46×46		
AP400			F25	55×55		

Controlval®
Representante Exclusivo Lationamérica
+56 9 4458 4722
ventas@controlval.cl
www.control-val.cl